



© lalegno

Dimension plank

LENGTH	23-2/3" (600 mm)
WIDTH	5-3/8" (135 mm)
TOTAL THICKNESS	5/8" (15 mm)

Dimension box

BOX LENGTH	24" (610 mm)
BOX WIDTH	11" (280 mm)
BOX THICKNESS	7" (180 mm)
BOX WEIGHT	51 lb
LAYERS/BOX	24
SQFT/BOX	20.88 sqft

Dimension pallet

PALLET LENGTH	39-1/3" (1000 mm)
PALLET WIDTH	47-1/4" (1200 mm)
PALLET HEIGHT	41-1/3" (1050 mm)
PALLET WEIGHT	2090 lb
BOX/PALLET	40
SQFT/PALLET	837.00 sqft

FEATURES

Top layer

WOOD TYPE	Oak
LATIN NAME	Quercus Robur
GRADE	PRIME
CONSTRUCTION	2-layer
BEVEL	Micro bevel 4 sides (0.5 mm)
SURFACE STRUCTURE	Brushed

Composition of the support

SUPPORT TYPE	Engineered
BASE OF THE SUPPORT	Plywood

Placement

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Tongue and groove	<ul style="list-style-type: none"> · Light household use · Moderate commercial use · Normal commercial use · Normal household use · Intensive commercial use 	Yes
		RE-SANDABLE
		Yes

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m ² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION



EN 14342

