



Dimension plank

| | |
|------------------------|-------------------------|
| LENGTH | 92 1/2" (2350 mm) RL |
| WIDTH | 7 1/2" (192 mm) |
| TOTAL THICKNESS | 5/8" (15 mm) |

Dimension box

| | |
|----------------------|-----------------|
| BOX LENGTH | 93" (2362 mm) |
| BOX WIDTH | 7 2/3" (195 mm) |
| BOX THICKNESS | 2 1/2" (64 mm) |
| BOX WEIGHT | 45 lb |
| LAYERS/BOX | 4 |
| SQFT/BOX | 19.42 sqft |

Dimension pallet

| | |
|----------------------|-------------------|
| PALLET LENGTH | 93 2/3" (2380 mm) |
| PALLET WIDTH | 38 1/2" (980 mm) |
| PALLET HEIGHT | 41 1/2" (1055 mm) |
| PALLET WEIGHT | 3375 lb |
| BOX/PALLET | 75 |
| SQFT/PALLET | 1456.50 sqft |

FEATURES

Top layer

| | |
|---------------------|-----------------------------------|
| WOOD TYPE | Oak |
| LATIN NAME | Quercus Robur |
| GRADE | CLASSIC |
| CONSTRUCTION | 2-layer |
| BEVEL | Micro bevel 2 long sides (0,5 mm) |

Composition of the support

| | |
|----------------------------|------------|
| SUPPORT TYPE | Engineered |
| BASE OF THE SUPPORT | Plywood |

Placement

| SYSTEM | APPLICATIONS | UNDERFLOOR HEATING |
|-------------------|---|--------------------|
| Tongue and groove | <ul style="list-style-type: none"> · Light household use · Moderate commercial use · Normal commercial use · Normal household use · Intensive commercial use | Yes |
| | | RE-SANDABLE |
| | | Yes |

TECHNICAL SPECIFICATIONS

| | Norm | Result |
|-----------------------|---------------------|------------------------|
| REACTION TO FIRE | EN 13501-1 | Dfl-S1 |
| FORMALDEHYDE EMISSION | EN 717-1 | E1 |
| PCP | CEN/TR 14823 | ≤ 5ppm |
| THERMAL CONDUCTIVITY | EN 12667 / ISO 8302 | 0,11m ² k/w |
| BIOLOGICAL DURABILITY | EN 335 | Class 1 |
| BREAKING STRENGTH | EN 1533 | Pass |
| SLIPPERINESS | EN 15676 | Pass |
| MOISTURE CONTENT | EN 13183-1 | 7% (+/-2%) |

CERTIFICATION



EN 14342

